

Float Valves

Float Valves for external installation on tanks NV 55



Level Regulating Valve

Technical Data

Connection DN	15 - 100
Nominal Pressure PN	16 - 40
Operating Pressure	0 - 4 bar
K _{vs} -Value	2.6 - 80 m ³ /h
Temperature	130 °C
Medium	liquids

Description

Float valves automatically control liquid levels in sealed or open (non-pressurised) tanks and vessels without requiring external energy. The float registers the liquid level and directly controls the valve via a lever. A change in the liquid level immediately results in a changed flow volume.

NV 55 is a single seated pipeline valve with tank connecting flange for vertical flow. The standard soft seal ensures perfect sealing of the valve.

The valves are fitted with a float bar on which a float featuring an inner tube is mounted (cylindrical float SC 8). By changing the position of the float on the bar the required liquid level is infinitely variable.

The following note applies to float valves fitted with float bars: If the liquid level is below the float bar i.e. if the float points downwards, a guide for the float bar should be installed.

When enquiring or ordering please quote the suffix letters given below:

Z = inlet. Valve closes when float rises

A = outlet. Valve closes when float drops

w = horizontal flow

o = upward flow

u = downward flow

r = includes sealed spindle

example: float valve Z/w (inlet valve for horizontal flow).

Standard

- » tank connecting flange
- » float bar stainless steel

Options

- » rubber or plastic coating for corrosive media
- » various seal materials suitable for your medium
- » spindle sealed against the tank (for example with Rießler plants)
- » special versions on request

Please state working pressure range when enquiring or ordering.

Operating instructions, know how and safety instructions must be observed. All the pressure has always been indicated as overpressure. We reserve the right to alter technical specifications without notice.



Pressure Ranges [bar] und K_{vs}-Values [m³/h]

pressure range bar	nominal diameter DN									
	15	20	25	32	40	50	65	80	100	
0 - 1	2.6	3.5	3.5	5.7	7.6	15	27	47	80	
0 - 4	2.6	3.5	3.5	5.7	7.6	7.6	15	27	47	

Float Valves

Float Valves for external installation on tanks NV 55

Level Regulating Valve



Materials

Body	cast steel optional CrNiMo-steel*
Cone and Seat	chromium steel optional CrNiMo-steel
Cone Guide	Rg optional CrNiMo-steel
Valve Seal	EPDM
Linkage	steel zincd or steel, optional CrNiMo-steel

* up to DN 100 made of CrNiMo-steel use NV 67e

Dimensions [mm] and Weights [kg] PN 10/16*

size	nominal diameter DN								
	15	20	25	32	40	50	65	80	100
A	130	150	160	180	200	230	290	310	350
B	180	180	180	200	200	200	300	300	300
C	55	55	55	125	125	125	105	105	105
D	95	95	95	115	115	115	175	175	175
E	210	210	210	280	280	280	420	420	420
F	30	30	30	40	40	40	60	60	60
H	100	100	100	125	125	125	200	200	200
kg	10	11	12	19	21	24	45	53	65

* PN 25/40 on request

Necessary Cylindrical Float ø SC 8 [mm] (ø = height)*

pressure range nominal diameter DN									
bar	15	20	25	32	40	50	65	80	100
0 - 1	200	200	200	200	200	240	280	280	305
0 - 4	240	240	240	240	280	280	305	340	420


*dimensions and weights see sheet no. SC 2.1....

Special designs on request.

The pressure has always been indicated as overpressure.

Mankenberg reserves the right to alter or improve the designs or specifications of the products described herein without notice.

Dimensional Drawing



Authorised Distributor:



**NATIONWIDE
OIL & GAS**

46, Jalan SS 22/21, Damansara Jaya,
47400 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Email: nog@nog.com.my

Web access: <http://www.nog.com.my>